



DIMENSION

Dim A	$(N-1) \times 3.81 + 4.70$
Dim B	$(N-1) \times 3.81$
Dim C	$(N-1) \times 3.81$

N= NUMBER OF CONCATS

Poles	Tolerance
2P-6P	± 0.15
7P-12P	± 0.20
13P-16P	± 0.25
17P-24P	± 0.35

SIGN	DATE	DESCRIPTION	APPROVER
△	03/24'12	Part No. is changed	Aaron
△	2012.05.22	Voltage rating is changed	Chen Bo
△			
△			

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item ① Male contact pin: Copper Tin plated
- Item ② Terminalhousing): Thermoplastic (UL94V-0)

Electrical: cULus /VDE

- Voltage rating: 300V/300V
- Current rating: 10A/10.5A
- Withstanding Voltage: 1.6 KV/2.5KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 250°C \pm 10°C/5 Sec
- Safety Approval:
- Critical dimension: ∇

OQ xx 3 2 x 0 xxxx G

No. OF POLES
02: 2 POLES
:
24: 24 POLES

COLOR
0 Black (RAL9005)
2 Red (RAL3001/D)
3 Orange(RAL2011/P)
4 Yellow(RAL1018/A)
5 Green(RAL6018/T)
6 Blue (RAL5015/A)
8 Grey(RAL7035/D)
9 White(RAL1102)
C Green(RAL6018/U)

G RoHS compliant (lead<4%)
In copper Alloy
0300: "@ " Logo (Standard)
030A: "ANYTEK" Mark
Any special item by customer request, please contact sales department.

ANYTEK				CUSTOMER COPY			
TITLE: OQ 3.81mm Series 180° (2P-24P) ---With hook							
PART NO. OQxx32x00300G/AG				DWG NO. 80Q0617			
APPROVED		CHECKED		DESIGNED		DRAWN	
				Chen Bo 05/23'12		Chen Bo 05/23'12	
CUST NO.				Tolerance			
				X. ± 0.50			
				X.X ± 0.30			
				X.XX ± 0.10			
				X° $\pm 1°$			
SHEET: 01/01				REV.: D			