



N = Number of poles  
 Dim A = N x 3.81  
 Dim B = (N-1) x 3.81

	Dim A	Dim B
2-6p	±0.15	±0.15
7-12p	±0.20	±0.20
13-18p	±0.25	±0.25
19-24p	±0.30	±0.30

SIGN	DATE	DESCRIPTION	APPROVER
△	11/01'05	Electrical standard changed.	Marvin
△	04/20'06	2p to 6p with wedge is changed.	Marvin
△	8/13'06	Added VDE standard	黎仁松
△	12/04'08	Add the tolerance table	Jacke
△	12/04'08	The temperature changed from -30°,105° to -40°,115°	Jacke
△	12/04'08	The wire entry hole was changed.	Jacke
△	2010.07.12	The solid and Stranded wire is changed from 16-26 to 16-28	Chen Bo
△	2010.07.12	Remove the CSA mark	Chen Bo

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material

- Item a Clamp: Brass(CuZn) Ni plated
- Item b Terminal screw: Steel Zinc plating "-" slot type
- Item c Female contact: PhBz, Tin plated
- Item d Terminal (housing): Thermoplastic (UL94V-0)
- Item e Terminal (cover): Thermoplastic (UL94V-0)

- △ △ Electrical cULus/VDE
  - Voltage rating: 300VAC/300VAC
  - Current rating: 10A/10.5A
  - Wire range: 1.5mm<sup>2</sup>
  - △ ● Solid wire(AWG): 16-28/16-28
  - Stranded wire(AWG): 16-28/16-28
  - Torque: 3Lb-In/0.2Nm
  - Screw: M2
  - Wire strip length: 6-7mm
  - Withstanding Voltage: 1.6KV/2.5KV
  - △ ● Operating temperature: -40°C to +115°C
  - △ ● Safety Approval:

TJ xx 31x 3 xxxx G

- 02 2 CONTACTS 0 Black (RAL9005)
  - 03 3 CONTACTS 2 Red (RAL3001/D)
  - ... .. 3 Orange(RAL2011/P)
  - 24 24 CONTACTS 4 Yellow(RAL1018/A)
  - 5 Green(RAL6018/T)
  - 6 Blue (RAL5015/A)
  - 8 Grey(RAL7035/D)
- RoHS  
Pb<40,000ppm
- 0000: "@" Logo  
000A: "ANYTEK" Mark  
Any special item by customer request.  
please contact sales department.

<b>ANYTEK</b>				<b>CUSTOMER COPY</b>				
								ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD
TITLE		TJ-3.81mm Series						
PART NO.		TJxx31x3xxxxG			DWG NO.		8TJ0601	
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance	
				Chen Bo 2010.07.12			UNIT: mm	X. ±0.50
							SHEET: 01/01	SCALE: NONE
							REV: H	X.XX ±0.10
								X° ±1°