



NOTE:

MATERIAL

HOUSING:

TPU, BLACK

CONTACT:

BRASS

NUT:

BRASS

SHELL:

BRASS

FINISH

CONTACT:

GOLD PLATED

OVER 50µ" NICKEL

NUT:

NICKEL PLATED

SHELL:

BRIGHT TIN PLATED

ELECTRICAL

RATED CURRENT:

1A

RATED VOLTAGE:

60V

WATER PROOF:

IP67

ENVIRONMENT

OPERATION TEMPERATURE: -40°C TO +85°C

WIRE GAUGE: 26-28 AWG

850-003-103RLSY

1 = GOLD FLASH  
4 = 10µ" GOLD

RoHS COMPLIANT

DO NOT SCALE FROM DRAWING



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF NorComp AND SHALL NOT BE REPRODUCED, COPIED OR USED AS THE BASIS FOR THE MANUFACTURE OR SALE OF APPARATUS WITHOUT WRITTEN PERMISSION.

DRAWN:

M. SIGMON

DATE:

03-04-16

CHECKED:

DATE:

NorComp

SCALE:

NTS

SHEET

OF

1

1

REV

0

DWG NO.

850-003-103RLSY