



P.C. Board Layout

REV.	SPECIFICATION	ECN NO.	APPD.

**Material:**  
 Housing: High Temperature Housing UL94V-0.  
 Contacts: Copper Alloy.

**Specification:**  
 Current Rating: 1 AMP.  
 Insulator Resistance: 1000M $\Omega$  min. at DC 500V.  
 Contact Resistance: 20m $\Omega$  max. at DC 100mA.  
 Operating Temperature: -55°C ~ +105°C.

**\*RoHS Compliant**

7902-A 09 F C 00 R 3 A  
 Series Position F: Female C: Selective Gold Plated 00: G/F R: Right Angle Type A: Tray Package

<b>Tolerances</b>	<b>Drawn No.</b>	7902D02012	
x = $\pm 0.50$	<b>Projection</b>		
.x = $\pm 0.25$	<b>Unit</b>	mm	<b>Scale</b> 1:1
.xx = $\pm 0.15$	<b>Drawn By</b>	Scott 08/25'16	

**Title:**  
 7902 Series  
 SLIM D-SUB  
 Right Angle Type

<b>OUPIN</b>			
OUPIN ELECTRONIC(KUNSHAN) CO., LTD.			
P/N: 7902-A09FC00R3A			
<b>SHEET</b>	1/1	<b>Ver.No.</b>	A4