



REV.	SPECIFICATION	ECN NO.	APPD.

Material:
 Housing: Thermoplastic Polyester UL94V-0, Black.
 Contacts: Copper Alloy.

Electrical Characteristics:
 Current Rating: 1.1 AMP.
 Insulator Resistance: 1000MΩ min.
 Contact Resistance: 30mΩ max.
 Dielectric Withstanding Voltage: AC 500V.
 Operating Temperature: -55°C~+85°C.
***RoHS Compliant**

8406- xx C 00 K U
 Series ————
 No. of Pin ————
 Count ————
 C: Selective Gold Plated
 U: Tube Package
 K: Straddle Mount
 00:G/F

Position	Dimension			
	A	B	C	D
36	7.65	6.00	25.00	9.15
64	21.65	20.00	39.00	23.15
98	38.65	37.00	56.00	40.15
164	71.65	70.00	89.00	73.15

Tolerances	Dwg. No.	8406D2003	
x = ±0.50	Projection	⊕ ↗	
.x = ±0.25	Unit	mm	Scale 1:1
.xx = ±0.15	Drawn By	Vic Lyu 05/14'15	

Title:
 8406 Series
 PCI Express
 Straddle Mount

OUPIN			
OUPIN ELECTRONIC(KUNSHAN) CO., LTD.			
P/N: 8406-xxC00KU			
SHEET	1/1	Ver.No.	A1