


9001 Series

DIN41612 B Type Female



Material:

Housing: Thermoplastic Polyester Glass Filled UL94V-0.

Contacts: Copper Alloy.

Electrical Characteristics:

Current Rating: 2 A.

Dielectric Withstanding Voltage: AC 1000V .


Insulator Resistance: 1000MΩ min.

Contact Resistance: 20mΩ max.

Operating Temperature: -55°C ~+125°C.

Features:

- * Mates with Male 2Row
- 9001-3164,3132 B Type.
- 9001-3364,3332 Q Type.



Length	1	2	W1	W2
X	4.0	2.5	13	17
Y	4.6	6.3	13	17
Pitch	Position	Rows with Contacts	Contact Arrange	
2.54mm	64	a b		
	32	a -		
5.08mm	32	a b		
	16	a -		

Ordering information


9001-	3	2	64	1	C	00	P	L1	A
Series	3: 2.54mm 4: 5.08mm	2: Female	Position	1: Dip Length 2: Dip Length W1: Dip Length W2: Dip Length	C: Selective Gold Plated	00: G/F	Blank: Dip P: Press Fit	Blank: W/O Lock L1: With Lock See Page CA03	A: Tray Package

9001 Series


DIN41612 Mating Introduce




2 Row insulator
B (Standard mounting)
Mounting axis
of the connector




3 Row insulator
C (Standard mounting)
Mounting axis
of the connector






Board lock available
L1=P.C.B. Thickness 1.6 ~2.0 mm
L2=P.C.B. Thickness 2.8 ~3.2 mm





Q (Reverse mounting)
Mounting axis
of the connector



R (Reverse mounting)
Mounting axis
of the connector




Board lock available
L1=P.C.B. Thickness 1.6 ~2.0 mm
L2=P.C.B. Thickness 2.8 ~3.2 mm




I.D.C. Type Ribbon Cable



2 Row insulator



3 Row insulator



Press Fit Type
2 Row insulator



3 Row insulator

