

https://www.phoenixcontact.com/cn/products/0708250



Panel feed-through terminal block - VDFK 4 - 0708250

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Panel feed-through terminal block, Connection method: Screw connection, Solder connection, Load current : 32 A, Cross section: 0.2 mm² - 6 mm², AWG 24 - 10, Connection direction of the conductor to plug-in direction: 0 °, Width: 10 mm, Color: gray

Why buy this product

- Easy fixing using plastic knurled nut or quick mounting wedge
- Touch-proof insulating housing
- Terminal blocks can be grouped
- Spacer plates increase clearances and creepage distances
- Universal screw connection with screw locking



Key Commercial Data

Packing unit	50 STK
Minimum order quantity	50 STK
GTIN	 4 017918 004576
GTIN	4017918004576
Custom tariff number	8536901900
Sales Key	AABBDA

Technical data

General

Number of levels	1
Number of connections	2
Nominal cross section	4 mm ²
Color	gray
Insulating material	PA
Flammability rating according to UL 94	V0
Rated surge voltage	6 kV
Degree of pollution	3

<https://www.phoenixcontact.com/cn/products/0708250>

Panel feed-through terminal block - VDFK 4 - 0708250

Technical data

General

Overvoltage category	III
Insulating material group	I
Connection in acc. with standard	IEC 60947-7-1
Nominal current I_N	32 A
Maximum load current	32 A
Nominal voltage U_N	500 V
Open side panel	No
Number of positions	1

Dimensions

Width	10 mm
Length	25.5 mm
Plate thickness	1 mm ... 4 mm

Connection data

Connection side	Outside
Connection method	Screw connection
Conductor cross section solid min.	0.2 mm ²
Conductor cross section solid max.	6 mm ²
Conductor cross section flexible min.	0.2 mm ²
Conductor cross section flexible max.	4 mm ²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	10
Conductor cross section flexible, with ferrule without plastic sleeve min.	0.25 mm ²
Conductor cross section flexible, with ferrule without plastic sleeve max.	4 mm ²
Conductor cross section flexible, with ferrule with plastic sleeve min.	0.25 mm ²
Conductor cross section flexible, with ferrule with plastic sleeve max.	4 mm ²
2 conductors with same cross section, solid min.	0.2 mm ²
2 conductors with same cross section, solid max.	1.5 mm ²
2 conductors with same cross section, stranded min.	0.2 mm ²
2 conductors with same cross section, stranded max.	1.5 mm ²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.	0.25 mm ²
2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.	1.5 mm ²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min.	0.5 mm ²
2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max.	1.5 mm ²
Stripping length	8 mm
Internal cylindrical gage	A4
Screw thread	M3
Tightening torque, min	0.6 Nm

https://www.phoenixcontact.com/cn/products/0708250



Panel feed-through terminal block - VDFK 4 - 0708250

Technical data

Connection data

Tightening torque max	0.8 Nm
Connection side	Inside
Connection method	Solder connection



Standards and Regulations

Connection in acc. with standard	CSA
	IEC 60947-7-1
Flammability rating according to UL 94	V0

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings



* Dimensions when using the DP-VDFK 4/4 spacer plate

Approvals

Approvals

Approvals

CSA / KEMA-KEUR / PRS / IECCE CB Scheme / EAC / cULus Recognized

Ex Approvals

ATEX

Approval details


<https://www.phoenixcontact.com/cn/products/0708250>




Panel feed-through terminal block - VDFK 4 - 0708250


Approvals


CSA		http://www.csagroup.org/services/testing-and-certification/certified-product-listing/	13631
	B	D	
mm ² /AWG/kcmil	28-10	28-10	
Nominal current IN	30 A	10 A	
Nominal voltage UN	300 V	300 V	

KEMA-KEUR		http://www.dekra-certification.com	2169260.01
mm ² /AWG/kcmil	4		
Nominal current IN	32 A		
Nominal voltage UN	500 V		

PRS		http://www.prs.pl/	TE/1825/880590/09
-----	---	---	-------------------

IECEE CB Scheme		http://www.iecee.org/	NL-29947
mm ² /AWG/kcmil	4		
Nominal current IN	32 A		
Nominal voltage UN	500 V		

EAC		B.01742
-----	---	---------

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	E60425-19770427
	B	C	D
mm ² /AWG/kcmil	30-10	30-10	30-10
Nominal current IN	30 A	30 A	10 A
Nominal voltage UN	300 V	150 V	300 V

<https://www.phoenixcontact.com/cn/products/0708250>



Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>