

<https://www.phoenixcontact.com/cn/products/1401444>

Network cable - VS-IP20-IP20-94B-LI/0,5 - 1401444

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Assembled Ethernet cable, shielded, 4-pair, 26 AWG stranded (7-wire), RAL 5021 (water blue), RJ45 connector/IP20 to RJ45 connector/IP20, line, length: 0.5 m

**Ethernet**

Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 557092
GTIN	4046356557092
Sales Key	ABNAEB

Technical data

Mechanical characteristics

Number of positions	8
Shielded	yes
Insertion/withdrawal cycles	≥ 750
Cable diameter	6.40 mm
Cable exit	straight
Cable structure	4x2xAWG26/7; S/FTP
Length of cable	0.5 m
Degree of protection	IP20
No. of cable outlets	1

Ambient conditions

Ambient temperature (operation)	-25 °C ... 60 °C (cable, fixed installation)
	-5 °C ... 60 °C (cable, flexible installation)
Degree of protection	IP20

Material data

Flammability rating according to UL 94	V2
Outer sheath, material	PUR

03/02/2017 Page 1 / 2

<https://www.phoenixcontact.com/cn/products/1401444>

Network cable - VS-IP20-IP20-94B-LI/0,5 - 1401444

Technical data

Material data

External sheath, color	water blue RAL 5021
------------------------	---------------------

Electrical characteristics

Number of positions	8
Degree of pollution	2

Standards and Regulations

Flammability rating according to UL 94	V2
--	----

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"