

https://www.phoenixcontact.com/cn/products/1403366



RJ45 connector - VS-PPC-C1-MNNA-4Q5-EMC - 1403366

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




Push/pull connector (version 14), metal EMC, with 4-pos. RJ45 QUICKON connector insert, with QUICKON fast connection technology, for 22 AWG 1-wire and 7-wire conductors, for 5.0 mm ... 8.0 mm cable diameter

Push/pull EMC connector



Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 708319
GTIN	4046356708319
Sales Key	ABNADA

Technical data

Mechanical characteristics

Standards/specifications	IEC PAS 61076-3-117
Number of positions	4
Connection profile	RJ45 8(4)
Locking type	Push Pull
Shielded	yes
Insertion/withdrawal cycles	≥ 500
Connection method	IDC fast connection
Conductor cross section	0.32 mm ² (solid) 0.36 mm ² (stranded)
Connection cross section AWG	22 ... 22 (solid) 22 ... 22 (stranded)
Max. cable diameter	5 mm ... 8 mm
External cable diameter	5 mm ... 8 mm
Cable exit	straight
Color	silver
Degree of protection	IP65/IP67

https://www.phoenixcontact.com/cn/products/1403366



RJ45 connector - VS-PPC-C1-MNNA-4Q5-EMC - 1403366

Technical data

Mechanical characteristics

No. of cable outlets	1
----------------------	---

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (assembly)	-5 °C ... 45 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C

Material data

Flammability rating according to UL 94	V0
Housing material	Zinc die-cast
Housing surface material	Nickel-plated
Contact carrier material	PC
Contact material	Copper alloy
Contact surface material	Gold over nickel
Material	Metal
O-ring material	NBR
Cable seal material	TPE
Material housing intermediate seal	NBR

Electrical characteristics

Number of positions	4
Nominal voltage U_N	50 V
Nominal current I_N	1.75 A
Transmission characteristics (category)	CAT5 (IEC 11801:2002)
GRP transmission properties	CAT5 (IEC 11801:2002)
Rated current	1.75 A
Overvoltage category	I
Degree of pollution	2
Contact resistance	0.001 Ω (Wire – IDC)
	0.005 Ω (Litz wires – IDC)
Rated voltage (III/3)	50 V

Standards and Regulations

Standards/regulations	IEC PAS 61076-3-117
Flammability rating according to UL 94	V0

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals

Approvals

<https://www.phoenixcontact.com/cn/products/1403366>



RJ45 connector - VS-PPC-C1-MNNA-4Q5-EMC - 1403366


Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.01742
-----	---	---------

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>