

https://www.phoenixcontact.com/cn/products/1404812



Y distributor - VS-PPC-J-1226-1227-1021-0,2 - 1404812

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


PROFINET Y distributor with assembled power line, 5-pos., IP65/IP67, 7/8" connector with metal housing on 2x socket in metal housing, cable length: 0.2 m



Y distributor with 7/8" connector



Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 320764
GTIN	4046356320764
Custom tariff number	8536909000
Sales Key	ABNADZ

Technical data

Mechanical characteristics

Number of positions	5
Shielded	No
Insertion/withdrawal cycles	≤ 100
Length of cable	0.2 m
Degree of protection	IP65/IP67

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C (cable, fixed installation)
	-5 °C ... 70 °C (cable, flexible installation)
	Plug / socket
Degree of protection	IP65
	IP67

Material data

Flammability rating according to UL 94	V0
Housing material	Zinc die-cast

<https://www.phoenixcontact.com/cn/products/1404812>



Y distributor - VS-PPC-J-1226-1227-1021-0,2 - 1404812

Technical data

Material data

Outer sheath, material	PVC
External sheath, color	silver-gray RAL 7001

Electrical characteristics

Rated voltage (III/3)	24 V
Rated current	16 A

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Line characteristics

Conductor cross section	1.5 mm ²
External cable diameter	8.10 mm
External sheath, color	silver-gray RAL 7001
Outer sheath, material	PVC
Conductor material	Bare Cu litz wires
Smallest bending radius, fixed installation	40 mm
Smallest bending radius, movable installation	150 mm

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.00767
-----	--	---------