

<https://www.phoenixcontact.com/cn/products/1405206>

Fiber optic coupling - VS-PPC-J-1-SCRJ-MNBK - 1405206

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

SC-RJ push-pull coupling, IP67, metal, with protective cover, color: nickel-plated



SCRJ push-pull coupling



Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 332804
GTIN	4046356332804
Custom tariff number	8536909000
Sales Key	ABNCDC

Technical data

Mechanical characteristics

Number of positions	2
Fiber type	GOF, PCF, POF
Insertion/withdrawal cycles	>= 500
Color	silver
Degree of protection	IP67

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
---------------------------------	------------------

Material data

Housing material	Zinc die-cast
Material	Metal

Electrical characteristics

Number of positions	2
Attenuation	0.2 dB (Acc. to IEC 61300-3-4)

Fiber optic coupling - VS-PPC-J-1-SCRJ-MNBK - 1405206

Technical data

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals

Approvals

Approvals
UL Listed / EAC

Ex Approvals

Approval details

UL Listed		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E308814-20070105
EAC		B.01742