

https://www.phoenixcontact.com/cn/products/1407819



Network cable - VS-PPC/PL-OE-94B-LI/5,0 - 1407819


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Assembled Ethernet cable, shielded, 4-pair, AWG 26 stranded (7-wire), RAL 5021 (sea blue), RJ45 connector/IP67 push/pull plastic housing to free cable end, line, length 5 m



Key Commercial Data

| | |
|----------------------|---|
| Packing unit | 1 STK |
| GTIN |  4 046356 475372 |
| GTIN | 4046356475372 |
| Custom tariff number | 8536909000 |
| Sales Key | ABNAEB |

Technical data

Dimensions

| | |
|-----------------|-----|
| Length of cable | 5 m |
|-----------------|-----|

Ambient conditions

| | |
|----------------------|------|
| Degree of protection | IP65 |
| | IP67 |

General data

| | |
|---------------------------------------|-----------------------|
| Number of positions | 8 |
| Signal type/category | Ethernet CAT5, 1 Gbps |
| Standards/regulations | IEC PAS 61076-3-117 |
| Degree of pollution | 2 |
| | 2 |
| Alternative short product description | Ethernet cable |
| Locking type | Push Pull |

Characteristics head 1

| | |
|-----------|-------------------------------------|
| Head type | Plug straight RJ45 Push Pull / IP67 |
|-----------|-------------------------------------|

https://www.phoenixcontact.com/cn/products/1407819



Network cable - VS-PPC/PL-OE-94B-LI/5,0 - 1407819

Technical data

Characteristics head 1

| | |
|--|---------|
| No. of positions (pin connector pattern) | 8 |
| Material (component) | Plastic |

Characteristics head 2

| | |
|--|----------------|
| Head type | free cable end |
| No. of positions (pin connector pattern) | 8 |

Standards and Regulations

| | |
|--|---------------------|
| Standards/regulations | IEC PAS 61076-3-117 |
| Flammability rating according to UL 94 | V2 |

Cable

| | |
|---|--|
| Cable type | Ethernet, flexible, CAT5 |
| Cable type (abbreviation) | 94B |
| UL AWM style | 20963 (80°C/30 V) |
| Signal type/category | Ethernet CAT5 (IEC 11801), 1 Gbps |
| Cable structure | 4x2xAWG26/7; SF/UTP |
| Conductor cross section | 4x 2x 0.14 mm ² |
| AWG signal line | 26 |
| Conductor structure signal line | 7x 0.16 mm |
| Core diameter including insulation | 0.96 mm |
| Wire colors | white/blue-blue, white/orange-orange, white/green-green, white/brown-brown |
| Twisted pairs | 2 cores to the pair |
| Overall twist | 4 pairs for core |
| Shielding | Aluminum-coated foil, tinned copper braided shield |
| Optical shield covering | 70 % |
| External sheath, color | water blue RAL 5021 |
| Outer sheath thickness | 1.05 mm |
| External cable diameter D | 6.4 mm ±0.2 mm |
| Minimum bending radius, fixed installation | 4 x D |
| Minimum bending radius, flexible installation | 8 x D |
| Tensile strength short-term/long-term | ≤ 100 N |
| Cable weight | 47 kg/km |
| Outer sheath, material | PUR |
| Material conductor insulation | Foamed PE |
| Conductor material | Bare Cu litz wires |
| Insulation resistance | ≥ 500 MΩ*km |
| Loop resistance | ≤ 290 Ω (per km) |
| Cable capacity | 48 nF/km (at 1 kHz) |
| Wave impedance | 100 Ω ±5 Ω (at 100 MHz) |
| Signal runtime | 5.3 ns/m |
| Coupling resistance | ≤ 100.00 mΩ/m (At 10 MHz) |

03/07/2017 Page 2 / 3

<https://www.phoenixcontact.com/cn/products/1407819>



Network cable - VS-PPC/PL-OE-94B-LI/5,0 - 1407819

Technical data

Cable

| | |
|---|---|
| Nominal voltage, cable | ≤ 100 V |
| Test voltage Core/Core | 700 V (50 Hz, 1 min.) |
| Test voltage Core/Shield | 700 V (50 Hz, 1 min.) |
| Flame resistance | according to IEC 60332-1-2 |
| Halogen-free | According to IEC 60754-1 |
| Resistance to oil | according to EN 60811-2-1 |
| Ambient temperature (operation) | -40 °C ... 80 °C (cable, fixed installation) |
| | -20 °C ... 80 °C (cable, flexible installation) |
| Ambient temperature (installation) | -20 °C ... 80 °C |
| Ambient temperature (storage/transport) | -20 °C ... 80 °C |

Environmental Product Compliance

| | |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 50 |
| | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

| | | |
|-----|--|---------|
| EAC | | B.00767 |
|-----|--|---------|

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>