

<https://www.phoenixcontact.com/cn/products/1409752>



Connector set - HC-KIT-B24-R02 - 1409752


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Connector set, consisting of: B24 sleeve housing and panel mounting base, 24-pos. plug and socket insert, M32 cable gland

RoHS

Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 752701
GTIN	4046356752701
Sales Key	BF7AFX

Technical data

Dimensions

Cable diameter	14 mm ... 21 mm
----------------	-----------------

General

Number of positions	24+PE
Design	B24
Rated voltage	500 V
Rated current	16 A
Connection method	Screw connection
Cable exit	lateral

<https://www.phoenixcontact.com/cn/products/1409752>



Connector set - HC-KIT-B24-R02 - 1409752

Articles in set

Contact insert - HC-B 24-I-UT-M - 1648296



HEAVYCON pin insert, B24 series, 24-pos., screw connection

Housing - HC-B 24-TFL-N-O1STM32S - 1460192



HEAVYCON B24 sleeve housing, for single locking latch, height: 65 mm, with 1 x M32 thread, lateral cable outlet

Housing - HC-B 24-AMLD - 1771943



HEAVYCON B24 panel mounting base, with single locking latch, height: 29 mm, with plastic cover, with flat gasket

Contact insert - HC-B 24-I-UT-F - 1648306



HEAVYCON female insert, B24 series, 24-pos., screw connection

Approvals

Approvals

Approvals

EAC / EAC

Ex Approvals

Approval details

<https://www.phoenixcontact.com/cn/products/1409752>



Connector set - HC-KIT-B24-R02 - 1409752

Approvals

EAC		7500651.22.01.00246
-----	--	---------------------

EAC		EAC-Zulassung
-----	--	---------------

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>