

https://www.phoenixcontact.com/cn/products/1411493



Connector set - HC-EVO-B24PT-BWSC-HH-M32ELC-AL - 1411493


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



EVO connector set, B24 series, metal housing, consisting of sleeve housing 1411473, panel mounting base 1411330, EVO screw connection 1411440, pin contact insert 1407736, socket contact insert 1407735



Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 932936
GTIN	4046356932936
Sales Key	BF7AFW

Technical data

General

Number of positions	24+PE
Design	B24
Cable exit	straight
	lateral
Degree of protection for housing	IP66
	IP67
	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Connection method	Push-in connection
Rated voltage (III/3)	500 V
Rated surge voltage	6 kV
Rated current	16 A

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

<https://www.phoenixcontact.com/cn/products/1411493>

Connector set - HC-EVO-B24PT-BWSC-HH-M32ELC-AL - 1411493

Articles in set

Contact insert - HC-B 24-I-PT-F - 1407735



Contact insert, Size: B24, Number of positions: 24+PE, Type of contact: Socket, Connection method: Push-in connection, Rated voltage: 500 V, Rated current: 16 A, Connection cross section: 0.14 mm² ... 2.5 mm², Application: Power

Contact insert - HC-B 24-I-PT-M - 1407736



HEAVYCON pin insert, B24 series, 24 + PE-pos., push-in connection

Cable gland - HC-B-G-M32-EC-AL - 1411440



EVO EMC cable gland with bayonet locking, B series, size M32, cable diameter: 14 - 21 mm

Housing - HC-STA-B24-BWSC-ELC-AL - 1411330



HEAVYCON B24 panel mounting base, with single locking latch, with plastic protective cover, with flat gasket, salt-water-resistant aluminum, conductive profile gasket.

Housing - HC-EVO-B24-HHFS-EL-AL - 1411473



HEAVYCON EVO sleeve housing, EMC version, without powder coating, with bayonet flange for EVO screw connection, B24, for single locking latch, height: 88 mm, without EVO screw connection.

Approvals

Approvals

<https://www.phoenixcontact.com/cn/products/1411493>



Connector set - HC-EVO-B24PT-BWSC-HH-M32ELC-AL - 1411493


Approvals

Approvals

EAC / EAC

Ex Approvals

Approval details

EAC		7500651.22.01.00246
-----	---	---------------------

EAC		EAC-Zulassung
-----	---	---------------

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>