https://www.phoenixcontact.com/cn/products/1414408



RJ45 connector - CUC-V06-C1PBK-S/R4CE8:1 - 1414408

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



RJ45 connector, Degree of protection: IP67, Number of positions: 8, 1 Gbps, CAT6, Material: PA, Connection method: Crimp connection, Connection cross section: AWG 24-27, Cable exit: straight



Ethernet

Key Commercial Data

Packing unit	1 STK
GTIN	4 055626 028309
GTIN	4055626028309
Sales Key	ABNAAA

Technical data

Mechanical characteristics

Number of positions	8
Connection profile	RJ45
Insertion/withdrawal cycles	≥ 750
Connection method	Crimp connection
Type of contact	Crimp contacts
Conductor cross section	0.1 mm ² 0.2 mm ² (stranded)
Connection cross section AWG	24 27 (stranded)
External cable diameter	5 mm 8.5 mm
Cable exit	straight
Color	black
Degree of protection	IP67
Design	RJ45, IP67, version 6
No. of cable outlets	1

Ambient conditions

Ambient temperature (operation)	-25 °C 60 °C
---------------------------------	--------------

Material data

02/28/2017 Page 1 / 3

https://www.phoenixcontact.com/cn/products/1414408



RJ45 connector - CUC-V06-C1PBK-S/R4CE8:1 - 1414408

Technical data

Material data

Flammability rating according to UL 94	V0
Housing material	PA
Contact carrier material	PC
Contact material	Phosphor bronze
Contact surface material	Gold
O-ring material	FPM
Cable seal material	NBR

Electrical characteristics

Number of positions	8
Nominal voltage U _N	50 V
Nominal current I _N	1.75 A
Transmission characteristics (category)	CAT6
GRP transmission properties	CAT6
Transmission speed	1 Gbps (250 MHz)
Frequency range	to 250 MHz
Rated current	1 A
Overvoltage category	I
Degree of pollution	2
Rated voltage (III/3)	125 V

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

02/28/2017 Page 2 / 3

https://www.phoenixcontact.com/cn/products/1414408



RJ45 connector - CUC-V06-C1PBK-S/R4CE8:1 - 1414408

Approvals

|--|

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com

02/28/2017 Page 3 / 3