

<https://www.phoenixcontact.com/cn/products/1416351>

## Connector set - HC-STA-B24PT-BWSC-LT-M32-ELCAL - 1416351


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Connector set, Number of positions: 24, Material: Die-cast aluminum, salt water resistant, Connection method: Push-in connection, Connection cross section: AWG 26-14



### Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 071220
GTIN	4055626071220
Sales Key	BF7BFX

### Technical data

#### General

Number of positions	24+PE
Design	B24
Connection method	Push-in connection
Degree of protection for housing	IP66
	IP67
	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Connection method	Push-in connection
Rated voltage (III/3)	500 V
Rated surge voltage	6 kV
Rated current	16 A

#### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

<https://www.phoenixcontact.com/cn/products/1416351>

## Connector set - HC-STA-B24PT-BWSC-LT-M32-ELCAL - 1416351

### Articles in set

#### Contact insert - HC-B 24-I-PT-F - 1407735



Contact insert, Size: B24, Number of positions: 24+PE, Type of contact: Socket, Connection method: Push-in connection, Rated voltage: 500 V, Rated current: 16 A, Connection cross section: 0.14 mm<sup>2</sup> ... 2.5 mm<sup>2</sup>, Application: Power

#### Contact insert - HC-B 24-I-PT-M - 1407736



HEAVYCON pin insert, B24 series, 24 + PE-pos., push-in connection

#### Housing - HC-STA-B24-BWSC-ELC-AL - 1411330



HEAVYCON B24 panel mounting base, with single locking latch, with plastic protective cover, with flat gasket, salt-water-resistant aluminum, conductive profile gasket.

#### Housing - HC-STA-B24-HLFS-1TTM32-EL-AL - 1412789



Sleeve housing B24, for single locking latch, Material: Die-cast aluminum, salt water resistant, Cable outlets: 1, straight, Height: 60 mm, Cable gland: none, Gland: no, 1x M32, Standard

#### Cable gland - G-INS-M32-M68N-NNES-S - 1411166



Cable gland, Cable gland material: Nickel-plated brass, External cable diameter 15 mm ... 21 mm, Shielding: No, Connecting thread: M32, Color: silver

## Approvals

### Approvals

<https://www.phoenixcontact.com/cn/products/1416351>



## Connector set - HC-STA-B24PT-BWSC-LT-M32-ELCAL - 1416351

### Approvals

Approvals

EAC / GL

---

Ex Approvals

---

### Approval details

EAC			7500651.22.01.00246
GL		<a href="http://exchange.dnv.com/tari/">http://exchange.dnv.com/tari/</a>	6196614 HH

---

Phoenix Contact 2017 © - all rights reserved  
<http://www.phoenixcontact.com>