

<https://www.phoenixcontact.com/cn/products/1420912>


Housing - HC-ADV-B10-HLWH-1TTM20-MF-BK - 1420912

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sleeve housing B10, Screw locking, Material: Die-cast aluminum, salt water resistant, Cable outlets: 1, straight, Height: 74 mm, Cable gland: none, Gland: no, 1x M20, Increased environmental requirements

Key Commercial Data

Packing unit	1 STK
Minimum order quantity	50 STK
GTIN	 4 055626 249117
GTIN	4055626249117
Sales Key	BF7AAA

Technical data

Dimensions

Height	74 mm
Width	57 mm
Length	105 mm
Length of the assembly cutout	65 mm
Width of the assembly cutout	35 mm

Ambient conditions

Degree of protection of housing (IP)	IP66
	IP68 (0.2 bar/24 h)
	IP69K (ISO 20653:2013-02)
Degree of protection of housing (NEMA)	4 (UL 50e)
	4X (UL 50e)
	12 (UL 50e)
Ambient temperature (operation)	-40 °C ... 125 °C

General

Note	For contact inserts HC-B10, BB18, DD42, M, K8/24
------	--

02/23/2017 Page 1 / 2

Housing - HC-ADV-B10-HLWH-1TTM20-MF-BK - 1420912

Technical data

General


Size	B10
Housing type	Sleeve housing
Locking type	Screw locking
Fixing screws	M6 (screw head: 5 mm Allen screw)
No. of cable outlets	1
Cable exit	straight
Screw connection	none
Type of the screw connection	1x M20
Housing material	Die-cast aluminum, salt water resistant
Housing surface material	Powder-coated, black
Seal material	Viton
Material lock	Stainless steel

Approvals

Approvals

Approvals
EAC
Ex Approvals

Approval details

EAC		7500651.22.01.00246
-----	---	---------------------