

<https://www.phoenixcontact.com/cn/products/1420914>



## Housing - HC-ADV-B16-HHWH-1STM25-MF-BK - 1420914


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Sleeve housing B16, Screw locking, Material: Die-cast aluminum, salt water resistant, Cable outlets: 1, lateral, Height: 93.7 mm, Cable gland: none, Gland: no, 1x M25, Increased environmental requirements

RoHS

### Key Commercial Data

|                        |   |
|------------------------|---|
| Packing unit           | 1 STK   |
| Minimum order quantity | 50 STK  |
| GTIN                   | <br>4 055626 249131 |
| GTIN                   | 4055626249131   |
| Sales Key              | BF7AAA  |

### Technical data

#### Dimensions

|                               |          |
|-------------------------------|----------|
| Height                        | 93.7 mm  |
| Width                         | 57 mm    |
| Length                        | 125.5 mm |
| Length of the assembly cutout | 86 mm    |
| Width of the assembly cutout  | 35 mm    |

#### Ambient conditions

|  |                           |
|--|---------------------------|
| Degree of protection of housing (IP)   | IP66                      |
|  | IP68 (0.2 bar/24 h)       |
|  | IP69K (ISO 20653:2013-02) |
| Degree of protection of housing (NEMA) | 4 (UL 50e)                |
|  | 4X (UL 50e)               |
|  | 12 (UL 50e)               |
| Ambient temperature (operation)        | -40 °C ... 125 °C         |

#### General

|      |   |
|------|---|
| Note | For contact inserts HC-B16, BB32, D40, DD72, HS6, HV6, M, K |
|------|---|

02/23/2017 Page 1 / 2

<https://www.phoenixcontact.com/cn/products/1420914>



# Housing - HC-ADV-B16-HHWH-1STM25-MF-BK - 1420914

## Technical data

### General

|                              |   |
|------------------------------|---|
| Size                         | B16                                     |
| Housing type                 | Sleeve housing                          |
| Locking type                 | Screw locking                           |
| Fixing screws                | M6 (screw head: 5 mm Allen screw)       |
| No. of cable outlets         | 1                                       |
| Cable exit                   | lateral                                 |
| Screw connection             | none                                    |
| Type of the screw connection | 1x M25                                  |
| Housing material             | Die-cast aluminum, salt water resistant |
| Housing surface material     | Powder-coated, black                    |
| Seal material                | Viton                                   |
| Material lock                | Stainless steel                         |

## Approvals

### Approvals

Approvals

EAC

Ex Approvals

### Approval details

|     |  |                     |
|-----|--|---------------------|
| EAC |  | 7500651.22.01.00246 |
|-----|--|---------------------|

Phoenix Contact 2017 © - all rights reserved  
<http://www.phoenixcontact.com>