

<https://www.phoenixcontact.com/cn/products/1460361>



## Housing - HC-B 6-TMB-100/O1STM20G-EEE - 1460361


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



HEAVYCON ADVANCE B6 sleeve housing, with bayonet locking (Allen screw), salt water resistant aluminum, height: 100 mm, with 1 x M20 thread, straight cable outlet, without surface; conductive seal (EMC properties)



### Key Commercial Data

Packing unit	10 STK
GTIN	 4 046356 592215
GTIN	4046356592215
Sales Key	BF7AAA

### Technical data

#### Dimensions

Height	100 mm
--------	--------

#### Ambient conditions

Degree of protection of housing (IP)	IP66
	IP67
Ambient temperature (operation)	-40 °C ... 125 °C

#### General

Note	For contact inserts HC-B6, BB10, DD24, M
Size	B6
Housing type	Sleeve housing
Locking type	Bayonet locking
Fixing screws	M6
No. of cable outlets	1
Cable exit	straight
Screw connection	none

<https://www.phoenixcontact.com/cn/products/1460361>



# Housing - HC-B 6-TMB-100/O1STM20G-EEE - 1460361

## Technical data

### General

Type of the screw connection	1x M20
Housing material	Die-cast aluminum, corrosion resistant
Housing surface material	Uncoated
Seal material	NBR, conductive
Material lock	Stainless steel
Connection	If insulating powder coating is present on the control cabinet panel, it should be removed from the profile gasket area in order to ensure optimum shielding.

## Approvals

### Approvals

---

Approvals

EAC

---

Ex Approvals

---

### Approval details

EAC		7500651.22.01.00246
-----	--	---------------------

---

Phoenix Contact 2017 © - all rights reserved  
<http://www.phoenixcontact.com>