

https://www.phoenixcontact.com/cn/products/1609293



## Cable - VS-P1222-P1226-C1021/ 1,0 - 1609293


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable, PROFINET/power, 5-position, PVC, silver-gray RAL 7001, Plug straight MSTB Push Pull / IP65, on Plug straight 7/8"-UNF / IP65, Cable length: 1 m



### Key Commercial Data

Packing unit	1 STK
GTIN	 4 046356 160889
GTIN	4046356160889
Custom tariff number	8536909000
Sales Key	ABNAGZ

### Technical data

#### Dimensions

Length of cable	1 m
-----------------	-----

#### Ambient conditions

Degree of protection	IP65
	IP67
Ambient temperature (operation)	-40 °C ... 70 °C (cable, fixed installation)

#### General data

Note	This product corresponds to the PROFINET Cabling and Interconnection Technology Guideline for PROFINET regulations, version 2.00, order no: 2.252, Chapter 11 Connectors for 24 Volt Power Supply Cabling and Chapter 13 Application specific Cabling and Interconnection Technology (AIDA)
Rated voltage	24 V
Number of positions	5
Signal type/category	PROFINET/power
Alternative short product description	PROFINET power cable
Rated voltage (III/3)	24 V

<https://www.phoenixcontact.com/cn/products/1609293>

## Cable - VS-P1222-P1226-C1021/ 1,0 - 1609293

### Technical data

#### Characteristics head 1

Head type	Plug straight MSTB Push Pull / IP65
No. of positions (pin connector pattern)	5

#### Characteristics head 2

Head type	Plug straight 7/8"-UNF / IP65
No. of positions (pin connector pattern)	5

#### Cable

Cable type	PVC gray
Cable type (abbreviation)	PVC
Conductor cross section	1.5 mm <sup>2</sup>
External sheath, color	silver-gray RAL 7001
Smallest bending radius, fixed installation	40 mm
Smallest bending radius, movable installation	150 mm
Outer sheath, material	PVC
Conductor material	Bare Cu litz wires

#### Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"