
https://www.phoenixcontact.com/cn/products/1652651



D-SUB gender changer - VS-09-GC-ST/ST - 1652651

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)







Key Commercial Data

Packing unit	10 STK		
Minimum order quantity	10 STK		
GTIN	4 017918 952792		
GTIN	4017918952792		
Custom tariff number	8536909000		
Sales Key	ABNJAE		

Technical data

Mechanical characteristics

Number of positions	9		
Insertion/withdrawal cycles	≥ 200		
Connection method	Gender changer		
Cable exit	straight		
Mounting type	Threads		
Design	D-SUB 9		
Size of housing	1		

Ambient conditions

Ambient temperature (operation)	-55 °C 125 °C
, , ,	

Material data

Flammability rating according to UL 94	V0		
Housing material	Steel, yellow chromated		
Contact carrier material	Polyester GF		
Contact material	Copper alloy		

03/09/2017 Page 1 / 2

https://www.phoenixcontact.com/cn/products/1652651



D-SUB gender changer - VS-09-GC-ST/ST - 1652651

Technical data

		ria		

ontact surface material Hard gold-plated over nickel			
Electrical characteristics			
Number of positions	9		
Rated current	5 A		
Overvoltage category	III		
Degree of pollution	2		
Rated voltage (III/3)	125 V		
Standards and Regulations			
Flammability rating according to UL 94 V0			
Environmental Product Compliance			
China RoHS	Environmentally Friendly Use Period = 50		
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"		

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC []

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com

03/09/2017 Page 2 / 2