https://www.phoenixcontact.com/cn/products/1652732



# RJ45 sleeve housings - VS-08-T-H-RJ45/IP67 - 1652732

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



RJ45 sleeve housings, Degree of protection: IP67, Number of positions: 8, Material: PA, Cable exit: straight

## Why buy this product

- High-quality and inexpensive solution in the IP protection zone
- ☑ IP65/67



## **Ethernet**

## **Key Commercial Data**

Packing unit	5 STK
Minimum order quantity	5 STK
GTIN	4 017918 952877
GTIN	4017918952877
Custom tariff number	8536909000
Sales Key	ABNACC

## Technical data

#### Mechanical characteristics

Number of positions	8
Insertion/withdrawal cycles	≥ 1000
External cable diameter	5 mm 8.5 mm
Cable exit	straight
Color	traffic grey A RAL 7042
Degree of protection	IP67
Design	RJ45, IP67, version 6
No. of cable outlets	1

#### Ambient conditions

Ambient temperature (operation)	-40 °C 80 °C

03/01/2017 Page 1 / 2

https://www.phoenixcontact.com/cn/products/1652732



# RJ45 sleeve housings - VS-08-T-H-RJ45/IP67 - 1652732

# Technical data

# Material data

Flammability rating according to UL 94	V0
Housing material	PA
O-ring material	FPM
Cable seal material	NBR
Material housing intermediate seal	NBR

#### Electrical characteristics

Number of positions	8
Overvoltage category	I
Degree of pollution	2
Rated voltage (III/3)	50 V

## Standards and Regulations

Flammability rating according to UL 94	V0

# **Environmental Product Compliance**

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

# Approvals

Approvals		
Approvals		

EAC

Ex Approvals

#### Approval details

EAC EHL	EAC-Zulassung
---------	---------------

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com

03/01/2017 Page 2 / 2