

<https://www.phoenixcontact.com/cn/products/1653061>


D-SUB contact insert - VS-25-A-DEVNET-LV - 1653061

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

D-SUB panel mounting frame, for DeviceNet, shell size 3, header, solder-in connection, unshielded, connection direction straight, IP67 degree of protection

*DeviceNet™*

Key Commercial Data

Packing unit	1 STK
GTIN	 4 017918 970017
GTIN	4017918970017
Custom tariff number	8536909000
Sales Key	ABNJCB

Technical data

Mechanical characteristics

Number of positions	5
Connection method	Solder connection
Type of contact	Pin
Degree of protection	IP67

Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
---------------------------------	------------------

Material data

Flammability rating according to UL 94	V0
Housing material	PA
Contact carrier material	PBT
Contact material	Cu alloy
Contact surface material	gold-plated

Electrical characteristics

Number of positions	5
---------------------	---

<https://www.phoenixcontact.com/cn/products/1653061>

D-SUB contact insert - VS-25-A-DEVNET-LV - 1653061

Technical data

Electrical characteristics

Rated current	8 A
Overvoltage category	III
Degree of pollution	3
Rated voltage (III/3)	250 V

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals


Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.01742
-----	---	---------

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>