

https://www.phoenixcontact.com/cn/products/1653155



RJ45 socket insert - VS-08-BU-RJ45-6-MOD/BU - 1653155


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



RJ45 socket insert, modular (Keystone), CAT6 (Link test), 8-position, shielded, socket on socket



Key Commercial Data

Packing unit	5 STK
Minimum order quantity	5 STK
GTIN	 4 017918 970079
GTIN	4017918970079
Custom tariff number	8536909000
Sales Key	ABNAAF

Technical data

Mechanical characteristics

Number of positions	8
Number of slots	1
Shielded	yes
Insertion/withdrawal cycles	≥ 750
Connection method	Female
Degree of protection	IP20

Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
---------------------------------	------------------

Material data

Flammability rating according to UL 94	V0
Contact carrier material	ABS
Contact material	Copper alloy
Contact surface material	Gold over nickel

<https://www.phoenixcontact.com/cn/products/1653155>



RJ45 socket insert - VS-08-BU-RJ45-6-MOD/BU - 1653155

Technical data

Electrical characteristics

Number of positions	8
Transmission characteristics (category)	CAT6 Link
Rated current	1.5 A
Degree of pollution	2
Rated voltage (III/3)	60 V

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.01742
-----	--	---------

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>