https://www.phoenixcontact.com/cn/products/1655195



# D-SUB contact support - VS-15-ST-DSUB-HD-CD-B - 1655195

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

D-SUB contact carrier, shell size 2, for 26 signal contacts, type of contact pin, for crimp contacts, straight, fixing with a 3 mm hole, for panel mounting frame and sleeve housing VS-15-...





# **Key Commercial Data**

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	4 046356 029131
GTIN	4046356029131
Custom tariff number	8536909000
Sales Key	ABNJCB

## Technical data

#### Mechanical characteristics

Number of positions	26
Connection profile	D-SUB 15
Insertion/withdrawal cycles	≥ 500
Connection method	Crimp connection
Mounting type	Hole
Design	15
Size of housing	2

### Ambient conditions

Ambient temperature (operation)	-55 °C 125 °C
, , ,	

#### Material data

Flammability rating according to UL 94	V0
Housing material	Steel, tin-plated
Contact carrier material	Polyester GF

03/10/2017 Page 1 / 2

https://www.phoenixcontact.com/cn/products/1655195



# D-SUB contact support - VS-15-ST-DSUB-HD-CD-B - 1655195

## Technical data

# Electrical characteristics

Number of positions	26
Rated current	3 A
Overvoltage category	III
Degree of pollution	2
Rated voltage (III/3)	60 V

## Standards and Regulations

Flammability rating according to UL 94	V0
--	----

## **Environmental Product Compliance**

China RoHS	Environmentally friendly use period: unlimited = EFUP-e	
	No hazardous substances above threshold values	

# Approvals

4	Approvals				
ļ	Approvals				

Ex Approvals

**EAC** 

## Approval details

EAC EHL	B.01742
---------	---------

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com

03/10/2017 Page 2 / 2