https://www.phoenixcontact.com/cn/products/1655328



D-SUB contact support - VS-15-BU-DSUB-3P-LH - 1655328

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

D-SUB contact carrier, shell size 2, accommodation for 3 combined contacts, type of contact socket, fixing with 4-40 UNC thread and solder pins, for panel mounting frame VS-15-...





Key Commercial Data

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	4 046356 029261
GTIN	4046356029261
Custom tariff number	8536909000
Sales Key	ABNJCB

Technical data

Mechanical characteristics

Number of positions	3
Insertion/withdrawal cycles	≥ 500
Connection method	Fitting to accept combined contact
Type of contact	Socket
Mounting type	Threads and solder pins
Design	D-SUB 15
Size of housing	2

Ambient conditions

Ambient temperature (operation)	-55 °C 125 °C
, , ,	

Material data

Flammability rating according to UL 94	V0
Housing material	Steel, yellow chromated
Contact carrier material	PBTP
Contact surface material	Gold over nickel

03/10/2017 Page 1 / 2

https://www.phoenixcontact.com/cn/products/1655328



D-SUB contact support - VS-15-BU-DSUB-3P-LH - 1655328

Technical data

	teristics

Liectrical Granacteristics			
Number of positions	3		
Standards and Regulations			
Flammability rating according to UL 94	V0		
Environmental Product Compliance			
China RoHS	Environmentally Friendly Use Period = 50		
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"		

Approvals

Approvals

Approvals

UL Recognized / EAC

Ex Approvals

Approval details

UL Recognized

http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm

FILE E 118976

EAC

EHE

B.01742

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com

03/10/2017 Page 2 / 2