https://www.phoenixcontact.com/cn/products/1658671



RJ45 sleeve housings - VS-08-T-H-RJ45/IP67-BK - 1658671

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



RJ45 sleeve housings, Degree of protection: IP67, Number of positions: 8, Material: PA, Cable exit: straight

Why buy this product

- High-quality and inexpensive solution in the IP protection zone
- ☑ IP65/67



Ethernet

Key Commercial Data

Packing unit	5 STK
Minimum order quantity	5 STK
GTIN	4 046356 163170
GTIN	4046356163170
Custom tariff number	8536909000
Sales Key	ABNACC

Technical data

Mechanical characteristics

Number of positions	8
Insertion/withdrawal cycles	≥ 1000
External cable diameter	5 mm 8.5 mm
Cable exit	straight
Color	jet black RAL 9005
Degree of protection	IP67
Design	RJ45, IP67, version 6
No. of cable outlets	1

Ambient conditions

Ambient temperature (operation)	-40 °C 80 °C

03/01/2017 Page 1 / 2

https://www.phoenixcontact.com/cn/products/1658671



RJ45 sleeve housings - VS-08-T-H-RJ45/IP67-BK - 1658671

Technical data

Material data

Flammability rating according to UL 94	V0
Housing material	PA
O-ring material	FPM
Cable seal material	NBR
Material housing intermediate seal	NBR

Electrical characteristics

Number of positions	8
Overvoltage category	
Degree of pollution	2
Rated voltage (III/3)	50 V

Standards and Regulations

Flammability rating according to UL 94	V0
Training to the state of the st	1 **

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e	
	No hazardous substances above threshold values	

Approvals

Approvals			

Approvals

EAC

Ex Approvals

Approval details

EAC	EAC	B.01742
-----	-----	---------

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com

03/01/2017 Page 2 / 2