

https://www.phoenixcontact.com/cn/products/1688609




## RJ45 socket insert - VS-08-BU-RJ45/LP-4 - 1688609

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

RJ45 socket insert, 4x, for PCB assembly, CAT5e, 8-pos., shielded, with angled solder pins



### Key Commercial Data

Packing unit	5 STK
Minimum order quantity	5 STK
GTIN	 4 017918 622374
GTIN	4017918622374
Custom tariff number	8536909000
Sales Key	ABNAAD

### Technical data

#### Mechanical characteristics

Number of positions	8
Number of slots	4
Connection profile	RJ45
Insertion/withdrawal cycles	≥ 750
Connection method	Solder connection
Degree of protection	IP20

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 85 °C
---------------------------------	------------------

#### Material data

Flammability rating according to UL 94	V0
Contact carrier material	Thermoplastic
Contact material	Copper alloy
Contact surface material	Gold over nickel

<https://www.phoenixcontact.com/cn/products/1688609>



# RJ45 socket insert - VS-08-BU-RJ45/LP-4 - 1688609

## Technical data

### Electrical characteristics

Number of positions	8
Transmission characteristics (category)	CAT5 (IEC 11801:2002)
Rated current	1.5 A
Overvoltage category	II
Degree of pollution	2
Rated voltage (III/3)	150 V

### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Approvals

### Approvals

Approvals

EAC

Ex Approvals

### Approval details

EAC		B.01742
-----	--	---------

Phoenix Contact 2017 © - all rights reserved  
<http://www.phoenixcontact.com>