

<https://www.phoenixcontact.com/cn/products/1688638>



RJ45 sleeve housings - VS-08-T-RJ45/IP 20 - 1688638


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



RJ45 sleeve housing IP20, for pin insert VS-08-ST-RJ45, with push-pull interlocking for panel mounting frames, for cable cross section 5.0 mm ... 6.5 mm



Key Commercial Data

Packing unit	5 STK
Minimum order quantity	5 STK
GTIN	 4 017918 607920
GTIN	4017918607920
Custom tariff number	8536909000
Sales Key	ABNAAC

Technical data

Mechanical characteristics

Insertion/withdrawal cycles	≥ 750
External cable diameter	5 mm ... 6.5 mm
Cable exit	straight
Color	gray
Degree of protection	IP20
Design	RJ45, IP20
No. of cable outlets	1

Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
---------------------------------	------------------

Material data

Flammability rating according to UL 94	V0
Housing material	PA

Standards and Regulations

<https://www.phoenixcontact.com/cn/products/1688638>

RJ45 sleeve housings - VS-08-T-RJ45/IP 20 - 1688638

Technical data

Standards and Regulations

Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>