

https://www.phoenixcontact.com/cn/products/1688696



## RJ45 sleeve housings - VS-08-T-RJ45/IP67 - 1688696


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



RJ45 sleeve housing, IP67, for pin insert VS-08-ST-RJ45, with push-pull interlocking for panel mounting frames, for cable cross section 5.0 mm ... 6.5 mm



### Key Commercial Data

Packing unit	5 STK
Minimum order quantity	5 STK
GTIN	 4 017918 863616
GTIN	4017918863616
Custom tariff number	8536909000
Sales Key	ABNACC

### Technical data

#### Mechanical characteristics

Insertion/withdrawal cycles	≥ 1000
External cable diameter	5 mm ... 6.5 mm
Cable exit	straight
Color	gray
Tightening torque max.	2.5 Nm
Degree of protection	IP67
Design	RJ45, IP67, version 6
No. of cable outlets	1

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
---------------------------------	------------------

#### Material data

Flammability rating according to UL 94	V0
Housing material	PA
O-ring material	FPM

<https://www.phoenixcontact.com/cn/products/1688696>



## RJ45 sleeve housings - VS-08-T-RJ45/IP67 - 1688696

### Technical data

#### Material data

Cable seal material	NBR
---------------------	-----

#### Standards and Regulations

Flammability rating according to UL 94	V0
--	----

#### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

---

Phoenix Contact 2017 © - all rights reserved  
<http://www.phoenixcontact.com>