

<https://www.phoenixcontact.com/cn/products/1689323>

Contact insert - VS-PSC 1,5/5-M PE - 1689323

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

POWER-SUBCON header, for mounting side, 5-pos., with capacitive ground connection, shielded, color: green



RoHS

Key Commercial Data

Packing unit	10 STK
Minimum order quantity	10 STK
GTIN	 4 017918 893170
GTIN	4017918893170
Custom tariff number	8536909000
Sales Key	ABNJZZ

Technical data

Mechanical characteristics

Number of positions	5
Insertion/withdrawal cycles	≥ 100
Connection method	Printed circuit connection
Conductor cross section	0.14 mm ² ... 1.5 mm ²
Connection cross section AWG	28 ... 16
Mounting type	Threads
Insulation resistance	1 TΩ
Design	15
Size of housing	2

Ambient conditions

Ambient temperature (operation)	-20 °C ... 80 °C
---------------------------------	------------------

Material data

Flammability rating according to UL 94	V0
Contact carrier material	PA

03/14/2017 Page 1 / 3

Contact insert - VS-PSC 1,5/5-M PE - 1689323

Technical data

Material data

Contact material	Copper alloy
Contact surface material	Tin-plated

Electrical characteristics

Number of positions	5
Rated current	8 A
Overvoltage category	III
Degree of pollution	3
Rated voltage (III/3)	250 V

Standards and Regulations


Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance


China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Schematic diagram




Drilling diagram



Drilling diagram

Dimensional drawing



POWER SUBCON contact insert

Contact insert - VS-PSC 1,5/5-M PE - 1689323

Approvals

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.01742
-----	---	---------