

Pitch spacer - RZ-SPT 5-4 V - 1701535

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid
(<http://phoenixcontact.com/download>)




Accessories, Nominal current: 41 A, Nom. voltage: 1000 V, Pitch: 7.5 mm, Conductor/PCB connection direction: 90 °, Color: green

Why buy this product



Key Commercial Data

| | |
|------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit | 50 STK |
| Minimum order quantity | 50 STK |
| GTIN |  4 046356 543156 |
| GTIN | 4046356543156 |
| Sales Key | AABZAA |

Technical data

Dimensions

| | |
|--------------------------|---------|
| Pitch | 7.5 mm |
| Constructional height | 18.5 mm |
| Height | 23.1 mm |
| Length of the solder pin | 4.6 mm |
| Pin spacing | 14 mm |
| Hole diameter | 2.1 mm |

General

| | |
|-----------------------------|----------|
| Range of articles | SPT 5/-V |
| Rated surge voltage (III/3) | 8 kV |
| Rated surge voltage (III/2) | 8 kV |
| Rated surge voltage (II/2) | 6 kV |
| Rated voltage (III/3) | 800 V |
| Rated voltage (III/2) | 1000 V |

<https://www.phoenixcontact.com/cn/products/1701535>

Pitch spacer - RZ-SPT 5-4 V - 1701535

Technical data

General

| | |
|----------------------------------|-------------------|
| Rated voltage (II/2) | 1000 V |
| Connection in acc. with standard | EN-VDE |
| Nominal current I_N | 41 A |
| Nominal cross section | 6 mm ² |
| Stripping length | 15 mm |

Connection data

| | |
|-----------------------------------------------------------------------------------------|----------------------|
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.25 mm ² |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 1.5 mm ² |

Standards and Regulations

| | |
|----------------------------------|--------|
| Connection in acc. with standard | EN-VDE |
|----------------------------------|--------|

Environmental Product Compliance

| | |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |