

https://www.phoenixcontact.com/cn/products/1704836



Single PCB terminal block - PTSPL-6/1-2X2 2,1 R32 - 1704836


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



PCB terminal block for tin-plated stranded cables, e.g., type PV 1-F, nominal current: 41 A, 1-pos., connection method: spring-cage connection, mounting: THT/THR, user information on through hole reflow technology can be found at: combicon.com



Key Commercial Data

Packing unit	250 STK
Minimum order quantity	250 STK
GTIN	 4 046356 739757
GTIN	4046356739757
Custom tariff number	8536909000
Sales Key	AABCAA

Technical data

Dimensions

Length of the solder pin	2.1 mm
Pin dimensions	0,6 x 1
Hole diameter	1.3 mm

General

Nominal current I_N	41 A
Nominal cross section	6 mm ²
Solder pin surface	Sn
Stripping length	12 mm

Connection data

Conductor cross section flexible min.	2.5 mm ²
Conductor cross section flexible max.	6 mm ²
Conductor cross section flexible, with ferrule without plastic sleeve min.	2.5 mm ²
Conductor cross section flexible, with ferrule without plastic sleeve max.	6 mm ²

<https://www.phoenixcontact.com/cn/products/1704836>



Single PCB terminal block - PTSP-6/1-2X2 2,1 R32 - 1704836

Technical data

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals


Approvals


Approvals

cULus Recognized / EAC

Ex Approvals

Approval details

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm E365246-20141111
mm ² /AWG/kcmil		14-10
Nominal current I _N		30 A

EAC		B.01742
-----	-------------------------------------------------------------------------------------	---------

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>