https://www.phoenixcontact.com/cn/products/1841830



PCB terminal block - PT-SG/ 1 8X0,1-2 THR2,1 R24 - 1841830

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)



PCB terminal block without insulating housing for contacting, e.g., flat-ribbon conductors, contact pins or PCBs, nominal current: 41 A, 1-pos., connection method: spring connection, mounting: THT/THR, user information on THT/THR technology can be found under "Downloads"

Why buy this product













Key Commercial Data

Packing unit	250 STK
Minimum order quantity	250 STK
GTIN	4 046356 919661
GTIN	4046356919661
Sales Key	AABCAA

Technical data

Dimensions

Length of the solder pin	2.1 mm
Pin dimensions	0,5 x 1
Hole diameter	1.4 mm

General

Range of articles	PT-SG
Nominal current I _N	41 A
Nominal cross section	6 mm²
Solder pin surface	Sn
Number of positions	1

Connection data

Conductor cross section solid min.	0.25 mm²
Conductor cross section solid max.	2.5 mm ²

02/20/2017 Page 1 / 2

https://www.phoenixcontact.com/cn/products/1841830



PCB terminal block - PT-SG/ 1 8X0,1-2 THR2,1 R24 - 1841830

Technical data

Connection data

Conductor cross section flexible, with ferrule without plastic sleeve min.	0.25 mm²
Conductor cross section flexible, with ferrule without plastic sleeve max.	2.5 mm²
Conductor cross section flexible, with ferrule with plastic sleeve min.	0.25 mm ²
Conductor cross section flexible, with ferrule with plastic sleeve max.	2.5 mm²
Conductor cross section AWG min.	22
Conductor cross section AWG max.	14
Max. width of flat-ribbon conductor	8 mm
Min. height of flat-ribbon conductor	0.1 mm
Max. height of flat-ribbon conductor	2 mm
Stripping length	3.5 mm 7 mm (Avoid tensile force on the terminal point)

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals Approvals Approvals EAC Ex Approvals Approval details EAC EAC B.01742

Phoenix Contact 2017 © - all rights reserved http://www.phoenixcontact.com

02/20/2017 Page 2 / 2