

https://www.phoenixcontact.com/cn/products/1868733



## PCB terminal block - MKDS 1,5/ 2-B-5,08 - 1868733


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)




PCB terminal block, Nominal current: 17.5 A, Nom. voltage: 400 V, Pitch: 5.08 mm, Number of positions: 2, Connection method: Screw connection with tension sleeve, Mounting: Wave soldering, Conductor/PCB connection direction: 0 °, Color: green, Connections internally jumpered

### Why buy this product

- ✓ Well-known connection principle allows worldwide use
- ✓ Low temperature rise, thanks to maximum contact force
- ✓ Allows connection of two conductors
- ✓ Internal bridging for easily looping through potentials
- ✓ The latching on the side enables various numbers of positions to be combined



### Key Commercial Data

|                        |   |
|------------------------|---|
| Packing unit           | 50 STK  |
| Minimum order quantity | 50 STK  |
| GTIN                   | <br>4 017918 141875 |
| GTIN                   | 4017918141875   |
| Custom tariff number   | 8536909000  |
| Sales Key              | AAABEA  |

### Technical data

#### Dimensions

|                          |              |
|--------------------------|--------------|
| Length                   | 11.6 mm      |
| Pitch                    | 5.08 mm      |
| Dimension a              | 5.08 mm      |
| Constructional height    | 14 mm        |
| Length of the solder pin | 3.5 mm       |
| Pin dimensions           | 0,9 x 0,9 mm |
| Hole diameter            | 1.3 mm       |

#### General

<https://www.phoenixcontact.com/cn/products/1868733>



## PCB terminal block - MKDS 1,5/ 2-B-5,08 - 1868733

### Technical data

#### General

|  |   |
|--|---|
| Range of articles                      | MKDS 1,5/..-B   |
| Insulating material group              | I   |
| Rated surge voltage (III/3)            | 4 kV  |
| Rated surge voltage (III/2)            | 4 kV  |
| Rated surge voltage (II/2)             | 4 kV  |
| Rated voltage (III/3)                  | 250 V   |
| Rated voltage (III/2)                  | 400 V   |
| Rated voltage (II/2)                   | 630 V   |
| Connection in acc. with standard       | EN-VDE  |
| Nominal current $I_N$                  | 17.5 A  |
| Nominal cross section                  | 1.5 mm <sup>2</sup>                                       |
| Maximum load current                   | 24 A (with a 2.5 mm <sup>2</sup> conductor cross section) |
| Insulating material                    | PA  |
| Solder pin surface                     | Sn  |
| Flammability rating according to UL 94 | V0  |
| Internal cylindrical gage              | A1  |
| Stripping length                       | 7 mm  |
| Number of positions                    | 2   |
| Screw thread                           | M3  |
| Tightening torque, min                 | 0.5 Nm  |
| Tightening torque max                  | 0.6 Nm  |

#### Connection data

|   |                      |
|---|----------------------|
| Conductor cross section solid min.  | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.  | 2.5 mm <sup>2</sup>  |
| Conductor cross section flexible min.   | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible max.   | 1.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule without plastic sleeve min.            | 0.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule without plastic sleeve max.            | 1.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule with plastic sleeve min.               | 0.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve max.               | 1.5 mm <sup>2</sup>  |
| Conductor cross section AWG min.  | 26                   |
| Conductor cross section AWG max.  | 14                   |
| 2 conductors with same cross section, solid min.                                      | 0.14 mm <sup>2</sup> |
| 2 conductors with same cross section, solid max.                                      | 1 mm <sup>2</sup>    |
| 2 conductors with same cross section, stranded min.                                   | 0.14 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded max.                                   | 0.75 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min. | 0.25 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max. | 0.5 mm <sup>2</sup>  |

# PCB terminal block - MKDS 1,5/ 2-B-5,08 - 1868733

## Technical data

### Connection data

|   |                     |
|---|---------------------|
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 1 mm <sup>2</sup>   |

### Standards and Regulations


|  |        |
|--|--------|
| Connection in acc. with standard       | EN-VDE |
|  | CUL    |
| Flammability rating according to UL 94 | V0     |

### Environmental Product Compliance


|            |   |
|------------|---|
| China RoHS | Environmentally Friendly Use Period = 50  |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

## Drawings

Drilling diagram



Dimensional drawing



## Approvals

### Approvals

#### Approvals

SEV / CCA / IECCEB Scheme / EAC / cULus Recognized / CCA / IECCEB Scheme

#### Ex Approvals


### Approval details

<https://www.phoenixcontact.com/cn/products/1868733>




## PCB terminal block - MKDS 1,5/ 2-B-5,08 - 1868733


### Approvals

|                            |   |   |            |
|----------------------------|---|---|------------|
| SEV                        |  | <a href="https://www.electrosuisse.ch/en/meta/shop/product-certificates.html">https://www.electrosuisse.ch/en/meta/shop/product-certificates.html</a> | IK-3542-M1 |
| mm <sup>2</sup> /AWG/kcmil |   | 2.5   |            |
| Nominal current IN         |   | 24 A  |            |
| Nominal voltage UN         |   | 250 V   |            |


|     |         |
|-----|---------|
| CCA | IK-2722 |
|-----|---------|

|                 |   |   |         |
|-----------------|---|---|---------|
| IECEE CB Scheme |  | <a href="http://www.iecee.org/">http://www.iecee.org/</a> | CH-8225 |
|-----------------|---|---|---------|

|     |  |         |
|-----|--|---------|
| EAC |  | B.01742 |
|-----|--|---------|

|                            |   |   |                 |
|----------------------------|---|---|-----------------|
| cULus Recognized           |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E60425-19770427 |
|                            | B   | D   |                 |
| mm <sup>2</sup> /AWG/kcmil | 30-14   | 30-14   |                 |
| Nominal current IN         | 10 A  | 10 A  |                 |
| Nominal voltage UN         | 300 V   | 300 V   |                 |

|                            |         |       |
|----------------------------|---------|-------|
| CCA                        | IK-2722 |       |
| mm <sup>2</sup> /AWG/kcmil |         | 2.5   |
| Nominal current IN         |         | 24 A  |
| Nominal voltage UN         |         | 250 V |

|                            |   |   |         |
|----------------------------|---|---|---------|
| IECEE CB Scheme            |  | <a href="http://www.iecee.org/">http://www.iecee.org/</a> | CH-8225 |
| mm <sup>2</sup> /AWG/kcmil |   | 2.5   |         |
| Nominal current IN         |   | 24 A  |         |
| Nominal voltage UN         |   | 250 V   |         |