

https://www.phoenixcontact.com/cn/products/1884429



Housing - VC-MP-A3 - 1884429


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Panel mounting base, made of metal, powder-coated type 3, number of modules 4, cable screw connection Pg21



Key Commercial Data

Packing unit	5 STK
GTIN	 4 017918 164454
GTIN	4017918164454
Custom tariff number	8544421100
Sales Key	ABOADC

Technical data

Dimensions

Height	58 mm
--------	-------

Ambient conditions

Degree of protection	IP65/IP66/IP67
Ambient temperature (operation)	-40 °C ... 125 °C

General

Note	When using fiber optics, the bending radii of the cable manufacturers must be observed.
Design	VC3
Degree of protection	IP65/IP66/IP67
Locking type	Screw locking
Pg screw connection	none
Number of module slots	4
Housing material	Zinc die-cast
Housing surface material	Powder coating
Seal material	EPDM

<https://www.phoenixcontact.com/cn/products/1884429>



Housing - VC-MP-A3 - 1884429

Technical data

General

Ambient temperature (operation)	-40 °C ... 125 °C
---------------------------------	-------------------

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>