

<https://www.phoenixcontact.com/cn/products/1884597>

Housing - VC-MP-K4 - 1884597

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Coupling housing, made of metal, powder-coated type 4, number of modules 5, cable screw connection Pg21

Why buy this product

- ✓ Space-saving PE connection to metal housing
- ✓ Any position can be a PE contact

Key Commercial Data

Packing unit	5 STK
GTIN	 4 017918 164621
GTIN	4017918164621
Custom tariff number	8544421100
Sales Key	ABOADC

Technical data

Dimensions

Height	61 mm
--------	-------

Ambient conditions

Degree of protection	IP65/IP66/IP67
Ambient temperature (operation)	-40 °C ... 125 °C

General

Note	When using fiber optics, the bending radii of the cable manufacturers must be observed.
Design	VC4
Degree of protection	IP65/IP66/IP67
Locking type	Screw locking
Type of the screw connection	1x Pg21
Pg screw connection	none

02/27/2017 Page 1 / 2

Housing - VC-MP-K4 - 1884597

Technical data

General

Cable exit	lateral
Number of module slots	5
Housing material	Zinc die-cast
Housing surface material	Powder coating
Seal material	EPDM
Ambient temperature (operation)	-40 °C ... 125 °C

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Approvals

Approvals

--

Approvals

EAC

Ex Approvals

--

Approval details

EAC		EAC-Zulassung
-----	---	---------------

--