

<https://www.phoenixcontact.com/cn/products/1900882>

## Printed-circuit board connector - MC 1,5/ 2-ST1F-5,08 - 1900882

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)


Plug component, Nominal current: 8 A, Rated voltage (III/2): 320 V, Number of positions: 2, Pitch: 5.08 mm, Connection method: Screw connection with tension sleeve, Color: green, Contact surface: Tin



The figure shows a 10-position version of the product

### Why buy this product

- ✓ Well-known connection principle allows worldwide use
- ✓ Low temperature rise, thanks to maximum contact force
- ✓ Allows connection of two conductors
- ✓ Screwable flange for superior mechanical stability



### Key Commercial Data

|                        |                                                                                                         |
|------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit           | 50 STK                                                                                                  |
| Minimum order quantity | 50 STK                                                                                                  |
| GTIN                   | <br>4 017918 429287 |
| GTIN                   | 4017918429287                                                                                           |
| Custom tariff number   | 8536909000                                                                                              |
| Sales Key              | AAAEAA                                                                                                  |

### Technical data

#### Dimensions

|             |          |
|-------------|----------|
| Length      | 15.5 mm  |
| Height      | 11.1 mm  |
| Width       | 19.28 mm |
| Pitch       | 5.08 mm  |
| Dimension a | 5.08 mm  |

#### General

|                   |                  |
|-------------------|------------------|
| Range of articles | MC 1,5/...-ST1F  |
| Type of contact   | Female connector |

12/13/2016 Page 1 / 4

<https://www.phoenixcontact.com/cn/products/1900882>

## Printed-circuit board connector - MC 1,5/ 2-ST1F-5,08 - 1900882

### Technical data

#### General

|                                        |                                                        |
|----------------------------------------|--------------------------------------------------------|
| Number of positions                    | 2                                                      |
| Connection method                      | Screw connection with tension sleeve                   |
| Insulating material group              | I                                                      |
| Rated surge voltage (III/3)            | 4 kV                                                   |
| Rated surge voltage (III/2)            | 4 kV                                                   |
| Rated surge voltage (II/2)             | 4 kV                                                   |
| Rated voltage (III/3)                  | 250 V                                                  |
| Rated voltage (III/2)                  | 320 V                                                  |
| Rated voltage (II/2)                   | 630 V                                                  |
| Connection in acc. with standard       | EN-VDE                                                 |
| Nominal current $I_N$                  | 8 A                                                    |
| Nominal cross section                  | 1.5 mm <sup>2</sup>                                    |
| Maximum load current                   | 8 A (with 1.5 mm <sup>2</sup> conductor cross section) |
| Insulating material                    | PA                                                     |
| Flammability rating according to UL 94 | V0                                                     |
| Internal cylindrical gage              | A1                                                     |
| Stripping length                       | 7 mm                                                   |
| Screw thread                           | M2                                                     |
| Tightening torque, min                 | 0.22 Nm                                                |
| Tightening torque max                  | 0.25 Nm                                                |

#### Connection data

|                                                                                         |                      |
|-----------------------------------------------------------------------------------------|----------------------|
| Conductor cross section solid min.                                                      | 0.14 mm <sup>2</sup> |
| Conductor cross section solid max.                                                      | 1.5 mm <sup>2</sup>  |
| Conductor cross section flexible min.                                                   | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible max.                                                   | 1.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule without plastic sleeve min.              | 0.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule without plastic sleeve max.              | 1.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule with plastic sleeve min.                 | 0.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve max.                 | 0.5 mm <sup>2</sup>  |
| Conductor cross section AWG min.                                                        | 28                   |
| Conductor cross section AWG max.                                                        | 16                   |
| 2 conductors with same cross section, solid min.                                        | 0.08 mm <sup>2</sup> |
| 2 conductors with same cross section, solid max.                                        | 0.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded min.                                     | 0.08 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded max.                                     | 0.75 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.   | 0.25 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.   | 0.34 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm <sup>2</sup>  |

Printed-circuit board connector - MC 1,5/ 2-ST1F-5,08 - 1900882

Technical data

Connection data

|                                                                                         |         |
|-----------------------------------------------------------------------------------------|---------|
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 0.5 mm² |
| Minimum AWG according to UL/CUL                                                         | 30      |
| Maximum AWG according to UL/CUL                                                         | 14      |

Standards and Regulations


|                                        |        |
|----------------------------------------|--------|
| Connection in acc. with standard       | EN-VDE |
|                                        | CUL    |
| Flammability rating according to UL 94 | V0     |

Environmental Product Compliance

|            |                                                                                                     |
|------------|-----------------------------------------------------------------------------------------------------|
| China RoHS | Environmentally Friendly Use Period = 50                                                            |
|            | For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration" |

Drawings

Dimensional drawing



Approvals

Approvals

|                                                                                        |
|----------------------------------------------------------------------------------------|
| Approvals                                                                              |
| VDE Gutachten mit Fertigungsüberwachung / IEC CB Scheme / CCA / cULus Recognized / EAC |

Ex Approvals

|                  |
|------------------|
| Approval details |
|------------------|

<https://www.phoenixcontact.com/cn/products/1900882>

## Printed-circuit board connector - MC 1,5/ 2-ST1F-5,08 - 1900882

## Approvals

|                                            |                                                                                   |                                                                                                                                                                                                              |          |
|--------------------------------------------|-----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|
| VDE Gutachten mit<br>Fertigungsüberwachung |  | <a href="http://www.vde.com/en/Institute/OnlineService/VDE-approved-products/Pages/Online-Search.aspx">http://www.vde.com/en/Institute/OnlineService/<br/>VDE-approved-products/Pages/Online-Search.aspx</a> | 40011723 |
|                                            |                                                                                   |                                                                                                                                                                                                              |          |
| mm <sup>2</sup> /AWG/kcmil                 |                                                                                   | 0.2-1.5                                                                                                                                                                                                      |          |
| Nominal current I <sub>N</sub>             |                                                                                   | 8 A                                                                                                                                                                                                          |          |
| Nominal voltage U <sub>N</sub>             |                                                                                   | 250 V                                                                                                                                                                                                        |          |

|                                |                                                                                   |                                                           |                |
|--------------------------------|-----------------------------------------------------------------------------------|-----------------------------------------------------------|----------------|
| IECEE CB Scheme                |  | <a href="http://www.iecee.org/">http://www.iecee.org/</a> | DE1-56063-B1B2 |
|                                |                                                                                   |                                                           |                |
| mm <sup>2</sup> /AWG/kcmil     |                                                                                   | 0.2-1.5                                                   |                |
| Nominal current I <sub>N</sub> |                                                                                   | 8 A                                                       |                |
| Nominal voltage U <sub>N</sub> |                                                                                   | 250 V                                                     |                |

|                                |                |         |  |
|--------------------------------|----------------|---------|--|
| CCA                            | CCA/ DE1 34219 |         |  |
|                                |                |         |  |
| mm <sup>2</sup> /AWG/kcmil     |                | 0.2-1.5 |  |
| Nominal current I <sub>N</sub> |                | 8 A     |  |
| Nominal voltage U <sub>N</sub> |                | 250 V   |  |

|                                |                                                                                     |                                                                                                                                                       |                 |
|--------------------------------|-------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------|
| cULus Recognized               |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | E60425-20110128 |
|                                | B                                                                                   | D                                                                                                                                                     |                 |
| mm <sup>2</sup> /AWG/kcmil     | 30-14                                                                               | 30-14                                                                                                                                                 |                 |
| Nominal current I <sub>N</sub> | 8 A                                                                                 | 8 A                                                                                                                                                   |                 |
| Nominal voltage U <sub>N</sub> | 300 V                                                                               | 300 V                                                                                                                                                 |                 |

|     |                                                                                     |         |
|-----|-------------------------------------------------------------------------------------|---------|
| EAC |  | B.01742 |
|-----|-------------------------------------------------------------------------------------|---------|