


https://www.phoenixcontact.com/cn/products/1980378



Base strip - ST 2,5-PCB/ 2-G-5,2 - 1980378

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



ST-COMBI receptacle, plug-in direction horizontal to the PCB, pitch: 5.2 mm, no. of positions: 2


The illustration shows the 5-pos. version

Why buy this product

- Universal plug-in solutions from the DIN rail through to the device can be implemented with the same plug
- The pitch width of this base strip is matched to that of the COMBI plug

RoHS

Key Commercial Data

Packing unit	50 STK
Minimum order quantity	50 STK
GTIN	 4 017918 972042
GTIN	4017918972042
Custom tariff number	8536909000
Sales Key	AABAAA

Technical data

Dimensions

Length	21.7 mm
Pitch	5.2 mm
Width	10.4 mm
Height	18.1 mm
Pin dimensions	1 x 1
Hole diameter	1.6 mm

General

Insulating material group	I
Maximum load current	24 A (with 4 mm ² conductor cross section)

<https://www.phoenixcontact.com/cn/products/1980378>



Base strip - ST 2,5-PCB/ 2-G-5,2 - 1980378

Technical data

General

Insulating material	PA
Flammability rating according to UL 94	V0
Internal cylindrical gage	A3
Number of positions	2

Standards and Regulations

Connection in acc. with standard	CUL
Flammability rating according to UL 94	V0

Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Approvals


Approvals


Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals

Approval details

UL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 60425
	B	C	
Nominal current IN	15 A	15 A	
Nominal voltage UN	300 V	300 V	


cUL Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm	FILE E 60425
	B	C	
Nominal current IN	15 A	15 A	
Nominal voltage UN	300 V	300 V	


<https://www.phoenixcontact.com/cn/products/1980378>



Base strip - ST 2,5-PCB/ 2-G-5,2 - 1980378

Approvals

EAC		B.01742
-----	---	---------

cULus Recognized		http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm
------------------	---	---

Phoenix Contact 2017 © - all rights reserved
<http://www.phoenixcontact.com>