


Plug-in card block - SKBI 64/B64 - 2263023

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plug-in card block, Nominal current: 1 A, Number of positions: 64, Pitch: 2.54 mm, Connection method: Screw connection with tension sleeve, Color: green

Why buy this product



Key Commercial Data

Packing unit	1 STK
GTIN	 4 017918 053871
GTIN	4017918053871
Custom tariff number	8536901900
Sales Key	AAAWAA

Technical data

Dimensions

Length	66 mm
Height	162 mm
Width	118 mm
Pitch	2.54 mm
Hole diameter	4.2 mm

General

Range of articles	SKBI 64
Connection in acc. with standard	EN-VDE
Nominal current I_N	1 A
Nominal voltage U_N	125 V (in acc. with DIN VDE 0110/Gr.B)
Nominal cross section	2.5 mm²
Stripping length	8 mm
Screw thread	M3

Plug-in card block - SKBI 64/B64 - 2263023

Technical data

General

Tightening torque, min	0.5 Nm
Tightening torque max	0.6 Nm
Number of positions	64

Connection data

Conductor cross section solid min.	0.2 mm²
Conductor cross section solid max.	4 mm²
Conductor cross section flexible min.	0.2 mm²
Conductor cross section flexible max.	2.5 mm²
Conductor cross section AWG min.	24
Conductor cross section AWG max.	12


Standards and Regulations

Connection in acc. with standard	EN-VDE
----------------------------------	--------

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings



Approvals

Approvals

Plug-in card block - SKBI 64/B64 - 2263023

Approvals

Approvals

EAC

Ex Approvals

Approval details

EAC		B.01742
-----	---	---------
