

HSF

NOTES:

Current Rating: 2.0AMP
Contact Resistance: 20mΩ Max
Withstand Voltage: 500V AC/DC
Insulation Resistance: 1000MΩ Min
Operation Temperature: -40°C to +105°C

Contact Material: Phosphor Bronze
Contact plating: Au Or Sn over Ni
Insulator Material: PA9T+30%G.F UL94V-0

Ordering Information

2243-1 XX R XX CUN T 1

No. of Pins per
Row: 02~40Pin

Contact Plating:
G0=Gold Flash
G3=10μ"Gold
G4=15μ"Gold
G5=30μ"Gold
S0=Gold Flash/Tin
S3=10μ"Gold/Tin
S4=15μ"Gold/Tin
S5=30μ"Gold/Tin
SN=Tin
SM=Matte Tin

Packing:
T=Tube
A=Tray

Item	Pitch	Mating
Standard	2.00	1215/1220
Alternate		

				OPERATION		DRAW JYHuang	DATE 2012/07/13	SCALE UNIT mm	FIT A4	PART NO. 2243-1XXRXXCUNT1		
				X.X	±0.40							
				X.XX	±0.25	CHECK	DATE	SIZE A4	SHEET 1/1	TITLE: FH2.00mm SINGLE ROW 90° DIP H=4.30		
				X.XXX	±0.15							
A0	2012/07/13	NEW		Angle	± 3°	APPROVE	DATE	SHEET 1/1	PROJ.	Customer NO.		
REV	DATE	MODIFICATION DESCRIPTION		DIM	TOL							

Recommended P.C.B Layout(Top Side)
(PCB BOARD TOLERANCE±0.05)

