

# HSF

NOTES:  
 Rated Current:3.0AMP.  
 Contact Resistance:20mΩ Max.  
 Withstand Voltage:1000V AC/DC  
 Insulation Resistance:1000MΩ Min.  
 Operation Temperature:-40°C to +105°C



Contact Material:Brass  
 Contact Plating:Au or Sn Over Ni  
 Insulator Material:PBT+30%G.F UL94V-0 BK(std)  
 or PA9T+30%G.F UL94V-0 BK

## Ordering Information



1125-12 XX XX S XXX X 1

No. of Pins Per Row:02-40	Contact Plating	Pin Length	Packing
G0=10u"Gold	G0=Gold Flash	L=A+B+2.5	0=PE Bag
G3=10u"Gold	Standard:085=8.5	T=Tube	
G4=15u"Gold	095=9.5		
G5=30u"Gold	105=10.5		
S0=Gold Flash/Tin	115=11.5		
S3=10u"Gold/Tin	118=11.8		
S4=15u"Gold/Tin	135=13.5		
S5=30u"Gold/Tin			

Item	Pin Length	A	B	Mating
Standard	8.50	3.00	3.00	2135
	9.50	3.00	4.00	2145
	10.50	3.00	5.00	2150
	11.50	3.00	6.00	2171 2185
	11.80	2.40	6.90	2171 2185
Alternate	13.50	3.00	8.00	



Recommended P.C.B Layout (Top Side)  
 (PCB BOARD TOLERANCE±0.05)



OPERATION	DRAW	DATE	SCALE	Fit	PART NO.
X.X ±0.40	William Chen	2012.05.28	UNIT mm		1125-12XXXXSXXXXX
X.XX ±0.25	CHECK	DATE	SIZE A4		TITLE: PH2.54 DUAL ROW 180° H=2.5
X.XXX ±0.15	APPROVE	DATE	SHEET 1/1		Customer NO.
Angle ± 3'			PROJ.		
DIM TOL					

**WCON**  
 Http: www.wcon.com

WCON-Dongguan  
 Tel: +86 769 85358920  
 Fax: +86 769 85358915  
 E-mail: sales@wcon.com

WCON-Kunshan  
 Tel: +86 512 57468408  
 Fax: +86 512 57468468  
 E-mail: sales@wcon.com