


HSF

NOTES:
 Current Rating: 1.0AMP
 Contact Resistance: 20mΩ Max
 Withstand Voltage: 500V AC/DC
 Insulation Resistance: 1000MΩ Min
 Operation Temperature: -40°C to +105°C


Contact Material: Phosphor Bronze
 Contact plating: Sn over Ni
 Insulator Material: PBT+15%G.F UL94V-0



Ordering Information

3900-XX MI SN ANT 0 2

No. of Pins	Contact Plating	Packing
04P 12P	SN=Tin	T=Tube
06P 14P		
08P 16P		
10P 18P		
20P		



Dimension & Ordering Information

Circuit	Part No.	Dimension		Q'ty /Tube
		A	B	
04	3900-04MISNANT02	8.45	2.54	68pcs
06	3900-06MISNANT02	10.99	5.08	52pcs
08	3900-08MISNANT02	13.53	7.62	42pcs
10	3900-10MISNANT02	16.07	10.16	36pcs
12	3900-12MISNANT02	18.61	12.70	31pcs
14	3900-14MISNANT02	21.15	15.24	27pcs
16	3900-16MISNANT02	23.69	17.78	24pcs
18	3900-18MISNANT02	26.23	20.32	22pcs
20	3900-20MISNANT02	28.77	22.86	20pcs

REV	DATE	MODIFICATION DESCRIPTION	CHANGE	OPERATION	DRAW	DATE	SCALE	FIT	PART NO.
				x.x ±0.40	JYHuang	2014/05/28	UNIT	mm	SEE TABLE
A1	2014/05/28	Micro Match --Mini Match	-----	x.xx ±0.25	CHECK	DATE	SIZE	A4	TITLE: Mini Match Box Header IDC type
A0	2012/10/12	NEW	-----	x.xxx ±0.15			SHEET	1/1	
				Angle ± 3'	APPROVE	DATE	PROJ.		Customer NO.
				DIM TOL					