

NOTES:

- ① THIS CONNECTOR IS DESIGNED TO MEET THE APPLICABLE PERFORMANCE REQUIREMENTS OF IEC 61076-4-101 AND BELLCORE GR-1217-CORE
- 2 RoHS DIRECTIVE COMPLIANCE, MAX SOLDERING TEMPERATURE 225°C.
- 3 CONNECTORS ARE END STACKABLE ON A 2.0 GRID.
- ④ FOR COMPLIANT CONTACT PLATED THRU HOLE REQUIREMENTS SEE THRU HOLE PLATING VIEW. MINIMUM P.C.BOARD THICKNESS 1.57 NOMINAL.
- ⑤ DIMENSIONS APPLY AFTER INSTALLATION IN P.C.BOARD.
- 6 CONNECTOR WITH MIXED PIN LENGTH.SELECTIVE LOADING PER PICMG™(COMPUTER TELEPHONY SPECIFICATIONS) 2.5 R1.0 APRIL 3, 1998 SEE SELECTIVE LOADING CHART AND LOADING PATTERN.
- ⑦ 0.2 MAX. GAP PERMISSIBLE TO P.C.BOARD

SPECIFICATIONS

MATERIALS

- ① Insulators: Thermoplastic Polyester, glass filled
Rated UL 94V-0, Color: Gray
- ② Pin contacts:
Copper Alloy
Finish: Mating Zone=Gold
Compliant Zone=Matte Tin
Performance Class 2= 250 cycles

PERFORMANCE CHARACTERISTICS ①

- Insulation resistance: 10000 megohms minimum
- Dielectric withstanding voltage(at sea level): 750 Vrms
- Current rating:
1 amp @70°C, fully loaded
1.5 amp @20°C, fully loaded
- Operating temperature range: -55°C to +125°C
- Contact resistance: 20 milliohms maximum






COMPLIANT CONTACT

- Max.Insertion Force(per contact): 22.5 lbs./100 N
- Min. Retention force(per contact): 4.5 lbs./20 N

	PDS.1	PDS.5	PDS.10	PDS.15	PDS.20
ROW f	6	6	6	6	6
ROW e	4	4	4	4	4
ROW d	4	4	4	4	4
ROW c	4	4	4	4	4
ROW b	4	4	4	4	4
ROW a	4	4	4	4	4
ROW z	6	6	6	6	6

SELECTIVE LOADING CHART				
PIN CODE	MATING LENGTH OF CONTACTS			CONTACT TAIL LENGTHS
	SIGNAL	ALL	GROUND	
	M	P	N	L
4	.209/5.30	.323/8.20	N/A	.146/3.70
6	.327/8.30	.441/11.20	.327/8.30	.146/3.70

SELECTIVE LOADING PATTERN

RECOMMENDED PC BOARD REQUIREMENTS
(COMPONENT SIDE BOARD SHOWN)THRU HOLE PLATING
SCALE 10:1

DESIGN UNITS ■ mm □ INCH			NAME: 2MM HEADER AB TYPE		Nextron® NEXTRONICS ENGINEERING CORP.							
GENERAL TOLERANCES: (UNLESS SPECIFIED)			PART NO: NX5ABBC11X01AA		TITLE: CUSTOMER DWG							
mm INCH			APPD: 楊海文 8/23'10		DWG. NO: 010-0000-719-NX5ABBC11X01AA							
4 PLACE ± 0.05 ±. **			CHKD: 廖小瓊 8/23'10		 <table><tr><td>SCALE:</td><td>SHEET:</td><td>REV:</td></tr><tr><td>1 / 1</td><td>1 / 1</td><td></td></tr></table>		SCALE:	SHEET:	REV:	1 / 1	1 / 1	
SCALE:	SHEET:	REV:										
1 / 1	1 / 1											
3 PLACE ± 0.10 ±. **			DRAWN: 何潔賢 8/23'10									
2 PLACE ± 0.20 ±. **												
1 PLACE ± 0.30 ±. **												
ANGULAR: ° ±. ** ° ±. **												

REV.	ECN. NO.	DESCRIPTION	DATE	DRAWN	APPD
A	**	Release	8/23'10	何潔賢	楊海文