

NOTES:

- 1 THIS CONNECTOR IS DESIGNED TO MEET THE APPLICABLE PERFORMANCE REQUIREMENTS OF IEC 61076-4-101 AND BELLCORE GR-1217-CORE
- 2 RoHS DIRECTIVE COMPLIANCE, MAX SOLDERING TEMPERATURE 225°C.
- 3 CONNECTORS ARE END STACKABLE ON A 2.0 GRID.
- 4 FOR COMPLIANT CONTACT PLATED THRU HOLE REQUIREMENTS SEE THRU HOLE PLATING VIEW. MINIMUM P.C.BOARD THICKNESS 1.57 NOMINAL.
- 5 DIMENSIONS APPLY AFTER INSTALLATION IN P.C.BOARD.
- 6 CONNECTOR WITH MIXED PIN LENGTH.SELECTIVE LOADING PER PICMG™(COMPUTER TELEPHONY SPECIFICATIONS) 2.5 R1.0 APRIL 3, 1998 SEE SELECTIVE LOADING CHART AND LOADING PATTERN.
- 7 0.2 MAX. GAP PERMISSIBLE TO P.C.BOARD

SPECIFICATIONS

MATERIALS


- 1 Insulators: Thermoplastic Polyester, glass filled
Rated UL 94V-0, Color: Gray
- 2 Pin contacts:
Copper Alloy
Finish: Mating Zone=Gold
Compliant Zone=Matte Tin
Performance Class 2= 250 cycles

PERFORMANCE CHARACTERISTICS 1

- Insulation resistance: 10000 megohms minimum
- Dielectric withstanding voltage(at sea level): 750 Vrms
- Current rating: 1 amp @70°C, fully loaded
1.5 amp @20°C, fully loaded
- Operating temperature range: -55°C to +125°C
- Contact resistance: 20 milliohms maximum




COMPLIANT CONTACT

- Max.Insertion Force(per contact): 22.5 lbs./100 N
- Min. Retention force(per contact): 4.5 lbs./20 N





SELECTIVE LOADING PATTERN

| PIN CODE | SELECTIVE LOADING CHART | | | CONTACT TAIL LENGTHS |
|----------|---------------------------|------------|-----------|----------------------|
| | MATING LENGTH OF CONTACTS | | | |
| | SIGNAL | ALL | GROUND | |
| | M | P | N | L |
| E | .268/6.80 | .382/9.70 | N/A | .571/14.50 |
| K | .327/8.30 | .441/11.20 | .327/8.30 | .630/16.00 |



RECOMMENDED PC BOARD REQUIREMENTS
(COMPONENT SIDE BOARD SHOWN)



THRU HOLE PLATING
SCALE 10:1

| | | | |
|---|----------------------------|---|---|
| DESIGN UNITS mm INCH | NAME: 2MM HEADER D TYPE | nexttron NEXTRONICS ENGINEERING CORP. | |
| GENERAL TOLERANCES: (UNLESS SPECIFIED) | PART NO: NX5D0AE01D54CA | TITLE: CUSTOMER DWG | C |
| 4 PLACE ±0.05 ±.*** | APPD: 楊海文 5/4'11 | DWG. NO: 010-0000-725-NX5D0AE01D54CA | |
| 3 PLACE ±0.10 ±.*** | CHKD: 廖小瓊 5/4'11 | SCALE: SHEET: REV.: | |
| 2 PLACE ±0.20 ±.*** | DRAWN: 何潔賢 5/4'11 | 1 / 1 1 / 1 A | |
| 1 PLACE ±0.30 ±.*** | | | |
| ANGULAR: X°±.*** X°±.*** | | | |

| | | | | | |
|------|----------|-------------|--------|-------|------|
| A | ** | Release | 5/4'11 | 何潔賢 | 楊海文 |
| REV. | ECN. NO. | DESCRIPTION | DATE | DRAWN | APPD |