



NOTES:  
 1.SCREW AND WASHER TO BE SHIPPED UNASSEMBLED IN A SEPARATE BAG  
 2.NO PLATING ON EDGES SHOWN  
 3.MATERIAL:  
 CONNECT:COPPER ALLOY PLATING:NI,BRIGHT TIN.  
 WASHER:STEEL PLATING Ni  
 SCREW :STEEL PLATING Ni  
 4.CURRENT RATING ,10 PIN:36AMP.@30°C RISE  
 5.OPERATING TEMPERATURE RANGE:-55°C TO +105°C

Preliminary Drawing

A	****	NEW REV ISSUANCE	5/25'10	劉林	楊海文
REV.	ECN. NO.	DESCRIPTION	DATE	DRAWN	APPD

DESIGN UNITS <input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH		NAME: POWER TERMINAL 10 PIN ASSY	 NEXTRONICS ENGINEERING CORP.	
GENERAL TOLERANCES: (UNLESS SPECIFIED)		PART NO: R-807B002101101	TITLE: CUST DWG.	C
4 PLACE	±****	±****	DWG. NO: 010-0000-688	
3 PLACE	±0.10	±0.040	SCALE:	SHEET:
2 PLACE	±0.20	±0.078	1 / 1	1 / 2
1 PLACE	±0.30	±0.118	REV.:	A
ANGULAR:	X°±2°	X°±2°	DRAWN: 劉林 5/25'10	