



NOTES:
 1.SCREW AND WASHER TO BE SHIPPED UNASSEMBLED IN A SEPARATE BAG
 2.MATERIAL:
 CONTACT:COPPER ALLOY PLATING BRIGHT TIN.
 WASHER:STEEL PLATING Ni
 SCREW :STEEL PLATING Ni
 3.CURRENT RATING :25AMP.@30°C
 4.OPERATING TEMPERATURE RANGE:-55°C TO +105°C
 5.PART NO EXPLANATION

Z-8 0 7 B * 0 2 1 0 1 0 8 1

SCREW SPEC

CODE	THREAD
0	#6-32 UNC-2B
1	M4

UNITS <input checked="" type="checkbox"/> mm <input type="checkbox"/> INCH		NAME: POWER TERMINAL 8 PIN ASSY WITHOUT HSG		NEXTRONICS ENGINEERING CORP.	
GENERAL TOLERANCES: (UNLESS SPECIFIED)		PART NO: Z-807B*02101081		TITLE: CUST DWG.	
	mm	INCH	APPD: SEAWEN 8/23'13		DWG NO: 010-0000-688
4 PLACE	±**	±.**	CHKD: PETER 8/23'13		C
3 PLACE	±0.10	±.004	DRAWN: LIUN 8/23'13		
2 PLACE	±0.20	±.007			SCALE: SHEET: REV.:
1 PLACE	±0.30	±.118			1 / 1 1 / 2 A
ANGULAR:	X°±2°	.X°±2°			

REV.	DESCRIPTION	DATE	APPD
A	RELEASE	8/23'13	SEAWEN